

Stromzangen | Current Probes Übersicht | Overview

Type	Order No.	Measurement Ranges	Bandwidth	DC-Measurement Accuracy	Current	Rise and Fall Time	Max. Working Voltage
TT-CC 220	15322	100 mV/A - 10 mV/A	DC - 300 kHz	±3% ±50mA @ 100 mV/A ±4% ±50mA @ 10 mV/A ±15% max @ 10 mV/A	10 A - 100 A	1.2 µs	600 VAC RMS CAT II 300 VAC RMS CAT III
TT-CC 550	15355	200 mV/A - 20 mV/A	DC - 500 kHz	±3% ±30mA @ 200 mV/A ±4% ±300mA @ 20 mV/A ±15% @ 200 mV/A	5 A - 50 A	0.7 µs	600 VAC RMS CAT II 300 VAC RMS CAT III
TT-CC 770	15377	500 mV/A - 50 mV/A	DC - 1 MHz	±3% ±20mA @ 500 mV/A ±4% ±200mA @ 50 mV/A ±15% @ 50 mV/A	7 A - 70 A	0.35 µs	600 VAC RMS CAT II 300 VAC RMS CAT III
TT-CC 990	15399	1 V/A - 100 mV/A	DC - 1.5 MHz	±3% ±10mA @ 1 V/A ±4% ±100mA @ 100 mV/A	4 A - 40 A	0.23 µs	600 VAC RMS CAT II 300 VAC RMS CAT III